

ST30B+C 4P grey

Varistor surge arresters T1 T2




Catalogue number	85201010
EAN code	5907813229299
Name of item	ST30B+C 4P grey
Collective packaging	1
Unit	pc

TECHNICAL SPECIFICATIONS

Width	70.8 mm
Height	90.5 mm
Rated voltage AC U_n	230 V
Max. continuous operating voltage U_c	275 V
Discharge current (I_n 8/20 μ s)	30 kA
Max. discharge current (I_{max} 8/20 μ s)	60 kA
Voltage protection level (U_p)	≤ 1.5 kV
Response time (t_A)	< 25 ns
Max. additional fuse (gL/gG)	125 A
Insulation resistance (R_{iso})	> 10^3 MΩ
Thermal overload protection	yes
Nominal cross-section of connected cables (rigid)	2.5...35 mm²
Nominal cross-section of connected cables (flexible)	2.5...25 mm²
Cross-section of remote signaling cables (rigid, flexible)	max 1.5 mm²
Operating temperature	-40 °C...+85 °C
Protection class	IP20
Mounting	on the rail TS 35

Additional information

The product under quality control in a proces monitored by TÜV Rheinland**ACCESSORIES****TS 35 metallic** - catalogue number 80035000

Installation rail TS 35

STDMM30B+C-275 orange - catalogue number 85201028

Varistor protection module T1 T2 (for ST30B+C 1P / ST30B+C 4P)